

LEGEND: S=Standard, O=Optional, P=Package, — = Not available

Complete package information is listed at the end of the Feature Availability section.

NOTE: Information shown is correct at time of publication, and is subject to change without notice.

2007 Dodge Caliber FEATURE AVAILABILITY

	SE	SXT	R/T AWD	FWD
EXTERIOR				
Badges				
Caliber badge _____	S	S	S	S
Body color liftgate appliqué _____	S	S	S	S
SXT badge _____	—	S	—	—
R/T badge _____	—	—	S	S
All-wheel-drive badge _____	—	—	S	—
Black-out tape _____	—	P	S	S
Colors: Inferno Red Crystal Pearl Coat, Solar Yellow Clear Coat), Sunburst Orange Pearl Coat, Marine Blue Pearl Coat, Steel Blue Metallic Clear Coat, Bright Silver Metallic Clear Coat, Black Clear Coat, Stone White Clear Coat and Light Khaki Metallic Clear Coat _____	O	O	O	O
Door Handles				
Black door handles _____	S	S	—	—
Bright door handles _____	—	—	S	S
Body Color Fascias _____	S	S	S	S
Fixed Long Mast Antenna _____	S	S	S	S
Grille				
Body color grille _____	S	—	—	—
Chrome grille _____	—	S	S	S
Lamps				
Halogen headlamps _____	S	S	S	S
Fog lamps _____	—	O/P	S	S
Daytime running lamp system _____	O	O	O	O
Mirrors				
Manual _____	S	—	—	—
Power _____	P	S	S	S
Moldings				
Body color bodyside _____	S	S	—	—
Chrome bodyside _____	—	—	S	S
Sill molding _____	—	—	S	S
Rear Spoiler _____	S	S	S	S
Rear Window Defroster _____	S	S	S	S
Sunroof, power express open/close _____	—	O	O	O
Windows				
Manual _____	S	—	—	—
Solar control glass _____	S	S	S	S
Power windows, driver one-touch _____	P	S	S	S
Wiper System				
Windshield, variable, intermittent _____	S	S	S	S
Rear window wiper/washer _____	S	S	S	S

	SE	SXT	R/T	
			AWD	FWD
INTERIOR				
Air Conditioning _____	O	S	S	S
Interior Colors: Pebble Beige, Pastel Slate Gray _____	O	O	O	O
Floor Covering				
Carpet _____	S	S	S	S
Vinyl washable and removable load floor covering _____	S	S	S	S
Console				
Full-length floor _____	S	S	S	S
Illuminated cup holders _____	S	S	S	S
12V auxiliary power outlet _____	S	S	S	S
115V auxiliary power outlet _____	—	S	S	S
Color-keyed PRNDL bezel _____	—	P	S	S
Satin Silver PRNDL bezel _____	S	S	P	P
Sliding armrest with cell phone holder _____	S	S	S	S
Floor Mats, front and rear _____	O	S	S	S
Instrument Cluster				
Electroluminescent cluster _____	S	S	S	S
120 mph primary speedometer _____	S	S	S	S
Outside temperature gauge _____	S	S	S	S
Instrument Panel				
<i>Chill Zone</i> [™] instrument panel cooler _____	P	S	S	S
Satin Silver bezel _____	S	S	P	P
Color-keyed bezel _____	—	P	S	S
Chrome switches _____	—	S	S	S
Lamps				
Front dome lamp _____	S	—	—	—
Cargo compartment lamp _____	S	—	—	—
Map/dome reading lamps _____	—	S	S	S
Removable/rechargeable lamp _____	—	S	S	S
Illuminated entry _____	—	S	S	S
Passenger Assist Handles _____	—	S	S	S
Mirrors				
Rearview day/night mirror _____	S	S	S	S
Rearview Auto Dim mirror _____	—	P	P	P
Seats				
Cloth low-back bucket seats _____	S	S	—	—
Cloth seats with color-keyed insert _____	—	P	S	S
Fold-flat front passenger seat _____	—	S	S	S
Driver height adjuster seat _____	—	S	S	S
YES Essentials® cloth seats _____	—	O	O	O
Flexible seating group _____	—	S	S	S
Folding flat load floor storage _____	S	S	S	S
Heated front seats _____	—	O	O/P	O/P
Marine Blue seat insert _____	—	P	P	P
Inferno Red seat insert _____	—	P	P	P
Sunburst Orange seat insert _____	—	P	P	P
Leather-trimmed bucket seats _____	—	P	P	P
Manual driver lumbar adjust _____	—	P	P	P
Rear 60/40 split recline seat _____	—	S	S	S
Sound System				
AM/FM CD radio with auxiliary audio input jack _____	S	S	S	S
AM/FM CD six-disc with cassette and MP3 capability _____	O	O	O	O
AM/FM CD six-disc with Full Map GPS Navigation Radio (late availability) _____	O	O	O	O
SIRIUS Satellite Radio _____	O	O	O	O
One-year service provided by SIRIUS _____	P	P	P	P
Speakers				
Four speakers _____	S	S	S	S
MusicGate Power [™] nine-speaker Boston Acoustic premium sound system, with				

subwoofer and two articulating liftgate speakers _____	O	O	O	O
Speed Control _____	—	O	S	S
Steering, power rack and pinion _____	S	S	S	S
Steering, performance _____	—	—	S	S
Steering Column, tilt _____	S	S	S	S
Steering Wheel				
Leather-wrapped _____	—	P	S	S
Steering wheel-mounted audio controls (must have speed control) _____		P	S	S
Sun Visors, sliding with mirrors _____	S	S	S	S
Electronic Vehicle Information Center _____	—	P	P	P
Tonneau Cover _____	O	P	S	S
UConnect® Hands-free Communication System _____	—	O	O	O

SE SXT RT
AWD FWD

POWERTRAIN AND CHASSIS

Engines:

1.8-liter 4 cyl. DOHC 16v VVT _____	S	S	—	—
2.0-liter 4-cyl. DOHC 16V VVT _____	O	O	—	—
2.4-liter 4-cyl. DOHC 16V VVT _____	—	—	S	S

Transmissions

Five-speed manual T355 _____	S	S	—	S
Continuously Variable Transaxle II (CVT2) _____	O	O	S	O
Auto Stick automatic _____	—	—	S	—

Brakes

Power front disc/rear drum _____	S	S	—	—
Anti-lock front disc/rear drum _____	O	O/P	—	—
Anti-lock four-wheel disc _____	—	P	S	S
Brake Assist _____	—	P	P	P

Engine Block Heater _____ O O O O

Engine Oil Cooler _____ P P P P

Exhaust Tip, chrome _____ — — S S

Fuel Tank

13.6 gal. _____	S	S	—	S
13.5 gal _____	—	—	S	—

Steering

Power, rack and pinion _____	S	S	—	—
Performance Steering _____	—	—	S	S

Suspension

Touring _____	S	S	—	—
Sport _____	—	—	S	S

Tires(a)

P205/70R15 BSW all-season _____	S	—	—	—
Dunlop brand tires _____	S	—	—	—
P215/60R17 BSW AS Touring _____	—	S	—	—
P215/55R18 BSW AS Performance _____	—	—	S	S
Firestone brand tires _____	—	S	S	S
Compact spare _____	S	S	S	S

Wheels

15 x 6.0 steel wheel _____	S	—	—	—
15" wheel covers _____	S	—	—	—
17 x 6.5 steel wheel _____	—	S	—	—
17" wheel covers _____	—	S	—	—
17 x 6.5 aluminum _____	—	O/P	—	—
18 x 7.0 aluminum _____	—	—	S	S
18 x 7.0 aluminum chrome clad _____	—	—	O	O

Trailer Tow Group _____ O O O O

(a) Another tire size or brand may also be used.

	SE	SXT	R/T	
			AWD	FWD
SAFETY AND SECURITY				
Air Bags				
Next generation multi-stage front air bags _____	S	S	S	S
Side window curtain front air bags _____	S	S	S	S
Side front seats air bags _____	O	O	O	O
Electronic Stability Program _____	—	O	O	O
Locks				
Manual locks _____	S	—	—	—
Speed sensitive power locks, includes liftgate _____	P	S	S	S
Occupant Classification System _____	S	S	S	S
Power Accessory Delay _____	S	S	S	S
Remote Keyless Entry _____	P	S	S	S
Security Alarm _____	—	P	P	P
Sentry Key® Engine Immobilizer _____	S	S	S	S
Tire Pressure Monitoring System _____	—	P	P	P
Universal Door Opener _____	—	P	P	P

(a) Certified to federal regulations that allow less forceful air bags. Always use seat belts. Remember, a back seat is the safest place for children.

(b) Always sit properly in the seat with the seat belt fastened. Always observe the passenger air bag indicator lamp to determine if the OCS classification is appropriate. Children 12 and under should always be in a back seat correctly using an infant or child restraint system or the seat belt positioned correctly for the child's age and weight.

	SE	SXT	R/T	
			AWD	FWD
EQUIPMENT GROUPS				
P1 – Driver Convenience Group includes compass and temperature gauge, universal garage door opener, electrochromic mirror, outside temperature gauge and tire pressure monitor _____	—	O	O	O
P2 – Leather Interior Group includes leather seats, heated front seats, leather-wrapped steering wheel and manual lumbar adjuster _____	—	O	O	O
P3 – Power Equipment Group includes driver one-touch power window, power locks, remote keyless entry and power mirrors _____	O	O	S	S
P4 – Security Group includes tonneau cover, security alarm and air filtration system _____	—	O	O	O
P5 – Sport Appearance Interior Group includes Pastel Slate Gray color with Red, Orange or Blue seat inserts that coordinate with the Exterior color, center stack and shifter bezels; cloth seats with colored Inserts, color-keyed PRNDL and IP bezels _____	—	O	S	S
P6 – Sport Package includes fog lamps, 17-inch aluminum wheels and Sport Appearance Package _____	—	P	S	S

SPECIFICATIONS

Dimensions are in inches (millimeters) unless otherwise noted.

General Information

Body Style _____ Sports Tourer
 Assembly Plant _____ Belvidere, Illinois
 EPA Vehicle Class _____ Compact car
 Introduction Date _____ January 2006, as 2007 model

Engine: 1.8-Liter DOHC 16-Valve I4 with DUAL VVT

Availability _____ Standard—SE and SXT
 Type and Description _____ Four cylinders in line, tuned intake manifold with Electronic Active Charge Motion Control valves
 Displacement _____ 109.7 cu. in. (1798 cu cm)

Bore x Stroke _____ 3.38 x 3.05 (86 x 77.4)
 Valve System _____ Chain-driven DOHC, 16 valves,
 electronically controlled dual Variable Valve Timing,
 direct-acting shimless mechanical bucket tappets
 Fuel Injection _____ Sequential, multi-port, electronic, returnless
 Construction _____ High-pressure die-cast aluminum block with dry iron liners,
 cast-aluminum cylinder head, cast-aluminum ladder frame
 forged steel crankshaft
 Compression Ratio _____ 10.5:1
 Power (SAE net, estimated) _____ 148 bhp (110 kW) @ 6,500 rpm (79.4 bhp/liter)
 Torque (SAE net, estimated) _____ 125 lb.-ft. (169 N•m) @ 5,200 rpm
 Max. Engine Speed _____ 6,750 rpm (electronically limited)
 Fuel Requirement _____ Unleaded regular, 87 octane (R+M)/2
 Oil Capacity _____ 5.0 qt. (4.7L) SAE 5W/20
 Coolant Capacity _____ 7.2 qt. (6.8L)
 Emission Controls _____ Single catalytic converter,
 dual heated oxygen sensors and engine features
 Smog-forming Pollution _____ 0.9 g/mile (0.56 g/km)^(a)
 Max. Gross Trailer Weight _____ 1,000 lbs. (450 kg)
 Estimated EPA Fuel Economy
 MPG (City/Hwy) _____ 28/32
^(a) NMOG + NOx emission limits under ULEV II and Tier 2, Bin 5 emission requirements.

Engine: 2.0-Liter DOHC 16-Valve I4 with DUAL VVT

Availability _____ Optional – SE and SXT
 Type and Description _____ Four cylinders in line, tuned intake manifold
 with electronic Active Charge Motion Control valves,
 dual counter-rotating balance shafts
 Displacement _____ 121.9 cu. in. (1998 cu cm)
 Bore x Stroke _____ 3.39 x 3.39 (86 x 86)
 Valve System _____ Chain-driven DOHC, 16 valves,
 electronically controlled dual Variable Valve Timing,
 direct-acting shimless mechanical bucket tappets
 Fuel Injection _____ Sequential, multi-port, electronic, returnless
 Construction _____ High-pressure die cast aluminum block with dry iron liners,
 cast-aluminum cylinder head, cast-aluminum ladder frame,
 Forged steel crankshaft
 Compression Ratio _____ 10.5:1
 Power (SAE net, estimated) _____ 158 bhp (117 kW) @ 6,400 rpm (79 bhp/liter)
 Torque (SAE net, estimated) _____ 141 lb.-ft. (191 N•m) @ 5,000 rpm
 Max. Engine Speed _____ 6,750 rpm (electronically limited)
 Fuel Requirement _____ Unleaded regular, 87 octane (R+M)/2
 Oil Capacity _____ 5.0 qt. (4.7L) SAE 5W/20
 Coolant Capacity _____ 7.2 qt. (6.8L)
 Emission Controls _____ Single catalytic converter,
 dual heated oxygen sensors and engine features
 Smog-Forming Pollution _____ 0.9 g/mile (0.56 g/km)^(a)
 Max. Gross Trailer Weight _____ 1,000 lbs. (450 kg) std., TBD with Trailer Tow Group^b
 Estimated EPA Fuel Economy
 MPG (City/Hwy) _____ 26/30
^(a) NMOG + NOx emission limits under ULEV II and Tier 2, Bin 5 emission requirements.
^(b) Not determined as of publication time.

Engine: 2.4-Liter DOHC 16-Valve I4 with DUAL VVT

Availability _____ Standard—R/T FWD and AWD
 Type and Description _____ Four cylinders in line, tuned intake manifold with
 Electronic Active Charge Motion Control valves
 dual counter-rotating balance shafts
 Displacement _____ 144 cu. in. (2360 cu cm)
 Bore x Stroke _____ 3.46 x 3.82 (88 x 97)

Valve System _____ Chain-driven DOHC, 16 valves,
electronically controlled dual Variable Valve Timing,
direct-acting shimless mechanical bucket tappets

Fuel Injection _____ Sequential, multi-port, electronic, returnless

Construction _____ High-pressure die-cast aluminum block with dry iron liners,
cast-aluminum cylinder head, cast-aluminum ladder frame,
forged steel crankshaft

Compression Ratio _____ 10.5:1

Power (SAE net, estimated) _____ 172 bhp (128 kW) @ 6,000 rpm (72 bhp/liter)

Torque (SAE net, estimated) _____ 165 lb.-ft. (223 N•m) @ 4,400 rpm

Max. Engine Speed _____ 6,500 rpm (electronically limited)

Fuel Requirement _____ Unleaded regular, 87 octane (R+M)/2

Oil Capacity _____ 5.0 qt. (4.7L) SAE 5W/20

Coolant Capacity _____ 7.2 qt. (6.8L)

Emission Controls _____ Single catalytic converter, FWD,
Dual catalytic converter, AWD,
Dual heated oxygen sensors and engine features

Smog-Forming Pollution _____ 0.9 g/mile (0.56 g/km)^(a)

Max. Gross Trailer Weight _____ 1,000 lbs. (450 kg)/2000 lbs. (900 kg) with Trailer Tow Group

Estimated EPA Fuel Economy

MPG (City/Hwy) _____ 26/30—FWD w/ 5-speed manual transaxle
_____ 24/27—FWD with CVT
_____ 23/26—AWD with CVT

^(a) NMOG + NOx emission limits under ULEV II and Tier 2, Bin 5 emission requirements.

Transaxle: Manual, Magna Driveline T355 5-Speed

Availability _____ Standard SE and SXT with 1.8L

Description _____ 5-speed, overdrive, synchronized in all forward ratios,
cable-operated, 3-plane shifter

Gear Ratios

1 st	_____	3.77
2 nd	_____	2.16
3 rd	_____	1.41
4 th	_____	1.026
5 th	_____	0.81
Reverse	_____	3.417
Final Drive Ratio	_____	4.12
Overall Top Gear	_____	3.34

Transmission: Automatic, CVT2

Availability _____ Standard with 2.0L and available 2.4L NAFTA markets

Description _____ Continuously variable ratio, lock-up torque converter, electronic controls

Gear Ratios

Forward	_____	2.349:1 to 0.394:1 continuously variable
Reverse	_____	1.762:1
Final Drive Ratio	_____	6.12:1
Overall Top Gear Ratio	_____	2.411

Drivetrain

Front-wheel Drive

Availability _____ Standard

All-wheel Drive

Availability _____ Optional with 2.4L engine

Type _____ Electromagnetically Controlled Coupling (ECC) with variable torque output

Rear Differential _____ Open

Electrical System

Alternator _____ 120-amp
 Battery _____ 525 CCA, maintenance-free

Dimensions and Capacities^a

Wheelbase _____ 103.7 (2635)
 Track, Front _____ 59.8 (1520)
 Track, Rear _____ 59.8 (1520)
 Overall Length _____ 173.8 (4413.9)
 Overall Width _____ 68.8 (1747.2)
 Overall Height _____ 60.4 (1533.1)
 Ground clearance _____ 7.0 (178)
 Frontal Area, sq. ft. (sq. m) _____ 24.5 (2.28)
 Drag Coefficient _____ 0.375

NATFA Curb Weight, lb. (kg)—Est. _____ SE 2,966 (1345)
 _____ SXT 3,039 (1378)
 _____ R/T FWD 3,156 (1432)
 _____ R/T AWD 3,308 (1501)
 NAFTA Weight Distribution, percent F/R _____ 58/42
 Fuel Tank Capacity, gal. (L) _____ 13.6 (51.5)—FWD
 _____ 13.5 (51.1)—AWD

(a) All dimensions measured at curb weight with standard tires

Accommodations

Seating Capacity, F/R _____ 2/3
 Front

Head Room without sunroof _____ 40.0 (1015.6)
 Leg Room _____ 41.8 (1061.5)
 Shoulder Room _____ 54.2 (1377.8)
 Hip Room _____ 52.2 (1325.3)
 Seat Travel _____ Driver—10.2 (260), passenger—10.2 (260)
 Recliner Angle Range, deg _____ Driver—up to 88, passenger—(76 fold flat/88 non-fold flat)
 SAE Front Volume Index, cubic ft. (cu. m) _____ 52.4 (1.485)

Rear Seat

Head Room _____ 38.9 (989.3)
 Leg Room _____ 35.6 (905.1)
 Knee Clearance _____ 0.9 (21.8)
 Shoulder Room _____ 53.4 (1357.2)
 Hip Room _____ 49.6 (1260.8)
 SAE Rear Seat Volume Index, cubic ft. (cu. m) _____ 42.8 (1.212)

SAE Interior Volume, cu. ft. (cu. m) _____ 95.2 (2.697)

Cargo Volume Indexes

Rear Seats Up, cu. ft. (cu. m) _____ 18.5 (0.525)
 Rear Seats Folded, cu. ft. (cu. m) _____ 48.0 (1.36)
 EPA Interior Volume Index, cu. ft. (cu. m) _____ 113.9 (3.225)
 Liftover Height _____ 27.6 (701.4)

Body

Layout _____ Transverse front-engine front-wheel drive or all-wheel drive
 Construction _____ Unitized steel body

Suspension

Front _____ Independent MacPherson strut,
 coil spring over gas-charged shock absorbers and stabilizer bar—Std.
 Rear _____ Multi-link-link independent with coil springs, link-type stabilizer bar,
 gas-charged shock absorbers—Std.

Steering

Type _____ Rack-and-pinion with hydraulic power assist
 Overall Ratio _____ 16.6:1
 Turning Diameter (curb-to-curb) _____ Front-wheel drive—35.5 ft. (10.8 m)

Steering Turns (lock-to-lock) _____ All-wheel drive—37.2 ft (11.3 m)
15- or 17-inch wheels and tires—2.88
18-inch wheels and tires—2.76

Tires^a

Availability _____ SE
Size and Type _____ P205/70R15 all-season
Mfr. and Model _____ Dunlop SP50
Revs per Mile (km) _____ 801 (1289)

Availability _____ SXT
Size and Type _____ P215/60R17 BSW AS Touring
Mfr. and Model _____ Firestone Affinity S3
Revs per Mile (km) _____ 760 (1223)

Availability _____ R/T
Size and Type _____ P215/55R18 AS Performance
Mfr. and Model _____ Firestone Firehawk GTA 03
Revs per Mile (km) _____ 765 (1231)

WHEELS

Availability _____ Standard SE
Type and Material _____ Stamped steel w/five-spoke wheel covers
Size _____ 15 x 6.0

Availability _____ Standard SXT
Type and Material _____ Stamped steel w/five-spoke wheel covers
Size _____ 17 x 6.5

Availability _____ Optional SXT
Type and Material _____ Machine-faced aluminum
Size _____ 17 x 6.5

Availability _____ Standard R/T
Type and Material _____ Machine-faced aluminum
Size _____ 18 x 7.0

Availability _____ Optional R/T
Type and Material _____ Chrome-clad aluminum
Size _____ 18 x 7.0

(a) Other sizes and brands may also be used

Brakes

Availability _____ Standard SE

Front

Size and Type _____ 10.8 x 1.0 (276 x 26) vented disc
with 2.2 (57) single-piston floating caliper
Swept Area^a _____ 205.36 sq. in. (1325.12 sq. cm)

Rear

Size and Type _____ 9.0 x 1.38 (229 x 35) drum
Swept Area _____ 78.1 sq. in. (503.6 sq. cm)

Power Assist Type _____ 10 (254) single-vacuum diaphragm
Four-Wheel Anti-Lock _____ Opt.—Included with CVT transmission

Availability _____ Standard SXT

Front

Size and Type _____ 11.5 x 1.0 (294 x 26) vented disc
with 2.2 (57) single-piston floating caliper
Swept Area _____ 223.52 sq. in. (1442.12 sq. cm)

Rear

Size and Type _____ 9.0 x 0.85 (229 x 35) drum
Swept Area _____ 78.1 sq. in. (503.6 sq. cm)

Power Assist Type _____ 10 (254) single-vacuum diaphragm
Four-Wheel Anti-Lock _____ Opt.—Included with CVT transmission

Availability _____ Standard R/T
Front

Size and Type _____ 11.5 x 1.0 (294 x 26) vented disc
with 2.2 (57) single-piston floating caliper

Swept Area _____ 223.52 sq. in. (1442.12 sq. cm)

Rear

Size and Type _____ 10.3 x 1.39 (262 x 10) solid disc
with 1.4 (35) single-piston floating caliper

Swept Area _____ 138.64 sq. in. (894.6 sq. cm)

Power Assist Type _____ 10 (254) single-diaphragm vacuum

Four-wheel Anti-lock _____ R/T

Electronic Stability Program^(b) _____ Optional SXT, R/T

(a) Note: Per axle

(b) Late Availability