

Canada: 2024 Ram 1500

SPECIFICATIONS

Specifications are based on the latest product information available at the time of publication.
All dimensions are in millimetres (inches) unless otherwise noted.
All dimensions measured at curb weight with standard tires and wheels.

GENERAL INFORMATION

Vehicle Type	Quad Cab and Crew Cab: 4x2, 4x4
Assembly Plant	Sterling Heights Assembly Plant, Sterling Heights, Michigan, U.S.A.
EnerGuide Vehicle Class	Standard Pickup

BODY/CHASSIS

Layout	4x2 — Longitudinal, front engine
	4x4 — Longitudinal, front engine, transfer case
Construction	4x2 — Ladder-type frame, steel cab, double-wall steel pickup box
	4x4 — Ladder-type frame, steel cab, double-wall steel pickup box

ENGINE: 3.6-LITRE PENTASTAR V-6 ETORQUE

Type and Description	60-degree gasoline V-6 with variable valve timing (VVT), V-type, liquid-cooled
Hybrid Battery	48-volt, 12-cell lithium-ion, nickel manganese cobalt (NMC) graphite chemistry, .43 kWh
Belt-starter Generator	9kW power, 90 lb.-ft. launch torque
Displacement	3,604 cu. cm (220 cu. in.)
Bore x Stroke	96.0 x 83.0 (3.78 x 3.27)
Valve System	Chain-driven DOHC, 24 valves and hydraulic end-pivot roller rockers
Fuel Injection	Sequential, multiport, electronic, returnless
Construction	Aluminum deep-skirt block, aluminum alloy heads
Compression Ratio	11.3:1
Power	305 hp (224 kW) @ 6,500 rpm
Torque	271 lb.-ft. (367 N•m) @ 4,900 rpm
Max. Engine Speed	6,400 rpm (electronically limited)
Fuel Requirement	Unleaded regular, 87 octane
Oil Capacity	5.7 litres (6.0 quarts)
Coolant Capacity	13.25 litres (14.0 quarts)
Emission Controls	Dual three-way catalytic converters, heated oxygen sensors
EnerGuide Fuel Economy L/100km (mpg – imp. gal.)	
(city/hwy/combined)	11.9/9.4/10.7 (24/30/26)

ENGINE: 5.7-LITRE HEMI® V-8 ETORQUE

Type and Description	90-degree gasoline V-8 with variable cam timing
Hybrid Battery	48-volt, 12-cell lithium-ion, nickel manganese cobalt (NMC) graphite chemistry, .43 kWh
Belt-starter Generator	12kW power, 130 lb.-ft. launch torque
Displacement	5,654 cu. cm (345 cu. in.)
Bore x Stroke	99.5 x 90.9 (3.92 x 3.58)
Valve System	Variable-cam timing, pushrod-operated overhead valves, 16 valves, hydraulic lifters with roller followers
Fuel Injection	Sequential, multiport, electronic, returnless
Construction	Deep-skirt cast-iron block with cross-bolted main bearing caps, aluminum-alloy heads with hemispherical combustion chambers
Compression Ratio	10.5:1
Power	395 hp (291 kW) @ 5,600 rpm
Torque	410 lb.-ft. (556 N•m) @ 3,950 rpm
Max. Engine Speed	5,800 rpm
Fuel Requirement	Unleaded mid-grade, 89 octane — recommended Unleaded regular, 87 octane — acceptable
Oil Capacity	6.6 litres (7.0 quarts)
Coolant Capacity	13.33 litres (14.0 quarts)
Emission Controls	Three-way catalytic converters, heated oxygen sensors and internal engine features
EnerGuide Fuel Economy L/100km (mpg – imp. gal.) (city/hwy/combined)	13.8/10.2/12.4 (20/28/23)

ENGINE: 6.2-LITRE HEMI® SUPERCHARGED V-8

Type and Description	90-degree V-type, liquid-cooled
Displacement	6,166 cu. cm (376 cu. in.)
Bore x Stroke	103.9 x 90.9 (4.09 x 3.58)
Valve System	Pushrod-operated overhead valves, 16 valves with sodium-filled exhaust valves and hollow stem intake valves, 16 conventional hydraulic lifters, all with roller tips
Fuel Injection	Sequential, multiport, electronic, returnless
Construction	Deep-skirt cast-iron block with cross-bolted main bearing caps, aluminum-alloy heads with hemispherical combustion chambers
Compression Ratio	9.5:1
Power	702 hp (523 kW) @ 6,100 rpm
Torque	650 lb.-ft. (882 Nm) @ 4,800 rpm
Max. Engine Speed	6,200 rpm (electronically limited)
Fuel Requirement	Premium 91 octane (R+M)/2 — required

Oil Capacity	7.4 litres (7.9 quarts)
Coolant Capacity	14.4 litres (15.0 quarts)
Factory Oil Fill	0W-40 Pennzoil Ultra synthetic
Emission Controls	Dual close-coupled two-way catalytic converters heated wide-range upstream and switching downstream O ₂ sensors and internal engine features
Exhaust Type	Dual 76 mm (3-in.) straight-thru exhaust system with dual 127 mm (5-in.) Black tips
EnerGuide Fuel Economy L/100km (mpg – imp. gal.) (city/hwy/combined)	23.5/16.8/19.6 (12/17/14)
Assembly Plant	Saltillo Engine Plant, Saltillo, Mexico

BASED ON 2023 ENERGUIDE FUEL CONSUMPTION RATINGS. GOVERNMENT OF CANADA TEST METHODS USED. YOUR ACTUAL FUEL CONSUMPTION WILL VARY BASED ON DRIVING HABITS AND OTHER FACTORS. FOR ENERGUIDE INFORMATION, PLEASE VISIT THE GOVERNMENT OF CANADA WEBSITE: WWW.VEHICLES.NRCAN.GC.CA

TRANSMISSION: TORQUEFLITE 850RE EIGHT-SPEED AUTOMATIC

Availability	Standard with 3.6-litre Pentastar V-6
Description	Adaptive electronic control, automatic or Electronic Range Select (ERS) manual control. Five-clutch-pack design with only two open clutches in any gear. Torque converter lock with turbine torsional damper for low lock-up speeds in 1st through 8th gear

TRANSMISSION: TORQUEFLITE 850RE EIGHT-SPEED AUTOMATIC (CONTINUED)

Gear Ratios	
1st	4.71
2nd	3.14
3rd	2.10
4th	1.67
5th	1.29
6th	1.00
7th	0.84
8th	0.67
Reverse	3.30
Axle Ratios	3.21, 3.55, 3.92 (Rebel only)

TRANSMISSION: TORQUEFLITE 8HP75 EIGHT-SPEED AUTOMATIC

Availability	Standard with 5.7-litre V-8 eTorque
Description	Adaptive electronic control, automatic or ERS manual control. Five-clutch-pack design with only two open clutches in any gear. Torque converter lock with turbine torsional damper for low lock-up speeds in 1st through 8th gear

Gear Ratios	
1st	4.71
2nd	3.14
3rd	2.10
4th	1.67
5th	1.29
6th	1.00
7th	0.84
8th	0.67
Reverse	3.30
Axle Ratios	3.21, 3.55, 3.92

TRANSMISSION: TORQUEFLITE 8HP95 EIGHT-SPEED AUTOMATIC

Availability	Standard with 6.2-litre HEMI supercharger V-8
Description	Adaptive electronic control with full manual control via gear selector or paddle shifters with six TRX-unique selectable modes: Sport, Snow, Tow, Mud, Baja and Auto (features performance shifting and gear holding feature)

Gear Ratios	
1st	4.71
2nd	3.14
3rd	2.11
4th	1.67
5th	1.29
6th	1.00
7th	0.84
8th	0.67
Reverse	3.30
Final Drive Ratio	2.62
Overall Top Gear	1.76
Axle Ratios	3.55

TRANSFER CASE: BW 48-12 PART-TIME

Availability	3.6-litre Pentastar V-6 4x4 with eTorque and 5.7-litre HEMI® V-8 eTorque
Shift Mechanism	Electric
Available Speeds	Two-speed
Operating Modes	2WD High; 4WD High, Locked; Neutral; 4WD Low, Locked
Low-range Ratio	2.64

Centre Differential Type	None
--------------------------	------

TRANSFER CASE: BW 48-11 ON-DEMAND

Availability	5.7-litre HEMI® V-8 eTorque
Shift Mechanism	Electric
Available Speeds	Two-speed
Operating Modes	2WD High; 4WD Auto; 4WD High, Locked; Neutral; 4WD Low, Locked
Low-range Ratio	2.64
Centre Differential Type	None

TRANSFER CASE: BW 48-13 FULL-TIME

Availability	6.2-litre HEMI® supercharged V-8 4x4
Shift Mechanism	Electric
Available Speeds	Two-speed
Operating Modes	4WD Auto, 4WD High, Locked; Neutral; 4WD Low, Locked
Torque Split, Front/Rear 25/75 Baja, 45/55 Mud/Sand and 50/50 Rock (in 4L)	Variable – 40/60 Auto, 45/55 Snow, 45/55 Tow, 30/70 Sport,
Low-range Ratio	2.64
Centre Differential Type	None

AXLES

Front	215mm
Rear	235mm (standard) with available open, limited-slip or electronic-locking differential 256mm (optional max tow with Dana Super 60 centre section) 256mm (standard Dana 60 with available open, limited slip or electronic locking differential on TRX)
Available Ratios	3.21, 3.55, 3.92

ELECTRICAL SYSTEM

Architecture	Powernet
Alternator	160-amp, 180-amp, 220-amp (Special Services Package), 250-amp (TRX)
Battery	Group 94R, low-maintenance H7 730 CCA (TRX – H7 AGM 80AH 800 CCA)

SUSPENSION

Front	Upper and lower A-arms, coil springs, twin-tube shock absorbers and stabilizer bar. Optional air suspension replaces twin-tube shock absorbers and progressive rate coil springs TRX – Upper and lower A-arms, coil springs, Bilstein e2 Blackhawk active performance shock absorber
Rear	Five-link with track bar, progressive rate coil springs, stabilizer bar, twin-tube shock absorbers, solid axle. Optional air suspension replaces progressive rate coil springs TRX – Five-link with track bar, coil springs, Bilstein e2 Blackhawk active damping twin-tube performance shock absorbers, solid axle

BRAKES

Front	
Size and Type	378 x 30 (14.9 x 1.2) vented disc with 57 mm (2.2 in.) two-piston pin-slider caliper and anti-lock braking system (ABS) TRX – 378 x 30 (15 x 1.2) inverted hat (outboard venting) rotors with 57 mm (2.2 in.) two piston pin-slider caliper and anti-lock braking system (ABS)
Swept Area	3,184 sq.cm (493.6 sq.in.)
Rear	
Size and Type	375 x 22 (14.8 x 0.87) disc with 57 mm (2.2 in.) single-piston pin-slider caliper and ABS TRX – 375 x 22 (15 x 0.87) disc with 57 mm (2.2 in.) single-piston pin-slider caliper and ABS
Swept Area	2,371.9 sq.cm (367.6 sq.in.)
Power-assist	Dual-rate, tandem diaphragm vacuum

STEERING

Power assist	Electric power steering
--------------	-------------------------

AIR BAGS

Quad Cab	6
Crew Cab	6

CARGO BOX

NOMINAL BOX SIZE	5FT., 7IN. (CREW)	6FT., 4IN. (REGULAR, QUAD OR CREW)
SAE volume, cu m (cu. ft.)	1.5 (53.9)	1.7 (61.5)
Length-at-Floor, Tailgate Closed	1,711 (67.4)	1,937 (76.3)

Cargo Width	1,687 (66.4)	1,687 (66.4)
Distance Between Wheelhouses	1,295 (51.0)	1,295 (51.0)
Depth	543 (21.4)	545 (21.5)
Tailgate Opening Width	1,525 (60.0)	1,525 (60.0)

EXTERIOR DIMENSIONS

QUAD CAB PICKUP, 6FT., 4IN. BOX

Model – Tire Size	4x2 - 275/55R20	4x4 - 275/55R20
Wheelbase (nominal)	3,569 (140.5)	3,569 (140.5)
Track, Front	1,741 (68.5)	1,741 (68.5)
Track, Rear	1,729 (68.1)	1,729 (68.1)
Overall Length	5,814 (228.9)	5,814 (228.9)
Overall Width	2,084 (82.1)	2,084 (82.1)
Overall Height	1,971 (77.6)	1,973 (77.7)

QUAD CAB PICKUP, 6FT., 4IN. BOX

Ground Clearance	4x2 - 275/55R20	4x4 - 275/55R20
Front Axle	199 (7.8)	208 (8.2)
Rear Axle	221 (8.7)	221 (8.7)
Open Tailgate to Ground	979 (34.6)	875 (34.4)
Pickup Body Height	545 (21.4)	545 (21.4)
Approach Angle, degrees	18.1	18.9
DEnerGuiderture Angle, degrees	25.2	25.0
Ramp Breakover Angle Without Skid Plate, degrees	19.5	19.9
Ramp Breakover Angle With Skid Plate, degrees	NA	17.8
Ground Clearance Without Skid Plate	213 (8.4)	221 (8.7)
Ground Clearance With Skid Plate	NA	208 (8.2)
Fuel Tank Capacity	87-litre (23-gal.) (standard) 98-litre (26-gal.) (standard)	87-litre (23-gal.) (standard) 98-litre (26-gal.) (standard)

Ground Clearance	4x2 - 275/55R20	4x4 - 275/55R20
	125-litre (33-gal.) (optional)	125-litre (33-gal.) (optional)

QUAD CAB PICKUP, 6FT., 4IN. BOX – AIR SUSPENSION, 4x2 AND 4x4

TIRE SIZE: 275/55R20

Suspension Mode	Entry / Exit	Normal Ride Height	Off Road 1	Off Road 2
Wheelbase (nominal)	3,569 (140.5)	3,569 (140.5)	3,569 (140.5)	3,569 (140.5)
Track, Front	1,741 (68.5)	1,741 (68.5)	1,741 (68.5)	1,741 (68.5)
Track, Rear	1,729 (68.1)	1,729 (68.1)	1,729 (68.1)	1,729 (68.1)
Overall Length	5,814 (228.9)	5,814 (228.9)	5,814 (228.9)	5,814 (228.9)
Overall Width	2,084 (82.1)	2,084 (82.1)	2,084 (82.1)	2,084 (82.1)
Overall Height	1,927 (75.9)	1,973 (77.7)	1,998 (78.7)	2,025 (79.7)
Front Axle	208 (8.2)	208 (8.2)	208 (8.2)	208 (8.2)
Rear Axle	221 (8.7)	221 (8.7)	221 (8.7)	221 (8.7)
Open Tailgate to Ground	836 (32.9)	875 (34.4)	893 (35.1)	925 (36.4)
Pickup Body Height	545 (21.4)	545 (21.4)	545 (21.4)	545 (21.4)
Approach Angle, degrees	14.4	18.9	21.5	23.1
Departure Angle, degrees	22.5	25.0	25.9	27.3
Ramp Breakover Angle Without Skid Plate, degrees	16.5	19.9	21.8	23.5
Ramp Breakover Angle With Skid Plate, degrees	14.4	17.8	19.7	21.3
Ground Clearance Without Skid Plate	169 (6.7)	221 (8.7)	251 (9.9)	273 (10.7)
Ground Clearance With Skid Plate	156 (6.1)	208 (8.2)	238 (9.4)	260 (10.2)
Fuel Tank Capacity	87-litre (23-gal.) (standard) 98-litre (26-gal.) (standard) 125-litre (33-gal.) (optional)	87-litre (23-gal.) (standard) 98-litre (26-gal.) (standard) 125-litre (33-gal.) (optional)	87-litre (23-gal.) (standard) 98-litre (26-gal.) (standard) 125-litre (33-gal.) (optional)	87-litre (23-gal.) (standard) 98-litre (26-gal.) (standard) 125-litre (33-gal.) (optional)

CREW CAB PICKUP

Model – Tire Size	4x2 – 275/55R20	4x2 – 275/55R20	4x4 – 275/55R20 4x4 – 325/65/R18 (TRX/5ft., 7in.)	4x4 – 275/55R20 4x4 – 325/65/R18 (TRX/5ft., 7in.)
Box Length	5ft., 7in.	6ft., 4in.	5ft., 7in.	6ft., 4in.
Wheelbase (nominal)	3,672 (144.6)	3,898 (153.5)	3,672 (144.6) TRX: 3,685.5 (145.1)	3,898 (153.5)
Track, Front	1,741 (68.5)	1,741 (68.5)	1,741 (68.5) TRX: 1,892.3 (74.5)	1,741 (68.5)
Track, Rear	1,729 (68.1)	1,729 (68.1)	1,729 (68.1) TRX: 1,882.14 (74.1)	1,729 (68.1)
Overall Length	5,916 (232.9)	6,142 (241.8)	5,916 (232.9)	6,142 (241.8)
Overall Width	2,084 (82.1)	2,084 (82.1)	2,084 (82.1) TRX: 2,235.2 (88)	2,084 (82.1)
Overall Height	1,968 (77.5)	1,966 (77.4)	1,971 (77.6) TRX: 2,054.86 (80.9)	1,968 (77.5)

CREW CAB PICKUP

Model – Tire Size	4x2 – 275/55R20	4x2 – 275/55R20	4x4 – 275/55R20 4x4 – 325/65/R18 (TRX/5ft., 7in.)	4x4 – 275/55R20 4x4 – 325/65/R18 (TRX/5ft., 7in.)
Ground Clearance	5ft., 7in.	6ft., 4in.	5ft., 7in.	6ft., 4in.
Front Axle	199 (7.8)	199 (7.8)	209 (8.2) TRX: 238.8 (9.4)	207 (8.1)
Rear Axle	220 (8.6)	220 (8.7)	220 (8.7) TRX: 203.2 (8.0)	220 (8.6)
Open Tailgate to Ground	877 (34.5)	875 (34.4)	872 (34.3) TRX: 967 (38.1)	871 (34.3)
Pickup Body Height	543 (21.4)	545 (21.4)	543 (21.4)	545 (21.4)
Approach Angle, degrees	18.0	18.1	19.0 TRX: 30.2	18.9
Departure Angle, degrees	25.1	25.0	24.9 TRX: 23.5	24.9
Ramp Breakover Angle Without Skid Plate, degrees	19.0	18.4	19.5 TRX: 21.9	18.7
Ramp Breakover Angle With Skid Plate, degrees	NA	NA	17.5	16.7

Model – Tire Size	4x2 – 275/55R20	4x2 – 275/55R20	4x4 – 275/55R20 4x4 – 325/65/R18 (TRX/5ft., 7in.)	4x4 – 275/55R20 4x4 – 325/65/R18 (TRX/5ft., 7in.)
Ground Clearance	5ft., 7in.	6ft., 4in.	5ft., 7in.	6ft., 4in.
Ground Clearance Without Skid Plate	211 (8.3)	212 (8.3)	222 (8.7)	220 (8.6)
Ground Clearance With Skid Plate	NA	NA	209 (8.2) TRX: 299.7 (11.8)	207 (8.1)
Fuel Tank Capacity	23-gal. (87-litre) (standard)	23-gal. (87-litre) (standard)	23-gal. (87-litre) (standard)	23-gal. (87-litre) (standard)
	26-gal. (98-litre) (standard)	26-gal. (98-litre) (standard)	26-gal. (98-litre) (standard)	26-gal. (98-litre) (standard)
	33-gal. (125-litre) (optional, standard on TRX)	33-gal. (125-litre) (optional, standard on TRX)	33-gal. (125-litre) (optional, standard on TRX)	33-gal. (125-litre) (optional, standard on TRX)

CREW CAB, 5FT., 7IN. BOX – AIR SUSPENSION, 4x2 AND 4x4

TIRE SIZE: 275/55R20

Suspension Mode	Entry / Exit	Normal Ride Height	Off Road 1	Off Road 2
Wheelbase (nominal)	3,672 (144.6)	3,672 (144.6)	3,672 (144.6)	3,672 (144.6)
Track, Front	1,741 (68.5)	1,741 (68.5)	1,741 (68.5)	1,741 (68.5)
Track, Rear	1,729 (68.1)	1,729 (68.1)	1,729 (68.1)	1,729 (68.1)
Overall Length	5,916 (232.9)	5,916 (232.9)	5,916 (232.9)	5,916 (232.9)
Overall Width	2,084 (82.1)	2,084 (82.1)	2,084 (82.1)	2,084 (82.1)
Overall Height	1,926 (75.8)	1,971 (77.6)	1,996 (78.6)	2,023 (79.6)
Front Axle	209 (8.2)	209 (8.2)	209 (8.2)	209 (8.2)
Rear Axle	220 (8.7)	220 (8.7)	220 (8.7)	220 (8.7)
Open Tailgate to Ground	833 (32.8)	872 (34.3)	890 (35.0)	923 (36.3)
Pickup Body Height	543 (21.4)	543 (21.4)	543 (21.4)	543 (21.4)
Approach Angle, degrees	14.6	19.0	21.7	23.3
Departure Angle, degrees	22.4	24.9	25.8	27.2
Ramp Breakover Angle Without Skid Plate, degrees	16.2	19.5	21.4	23.0
Ramp Breakover Angle	14.2	17.5	19.3	21.0

Suspension Mode	Entry / Exit	Normal Ride Height	Off Road 1	Off Road 2
With Skid Plate, degrees				
Ground Clearance Without Skid Plate	170 (6.7)	222 (8.7)	252 (9.9)	273 (10.8)
Ground Clearance With Skid Plate	157 (6.2)	209 (8.2)	239 (9.4)	261 (10.3)
Fuel Tank Capacity	87-litre (23-gal.) (standard)	87-litre (23-gal.) (standard)	87-litre (23-gal.) (standard)	87-litre (23-gal.) (standard)
	98-litre (26-gal.) (standard)	98-litre (26-gal.) (standard)	98-litre (26-gal.) (standard)	98-litre (26-gal.) (standard)
	125-litre (33-gal.) (optional)	125-litre (33-gal.) (optional)	125-litre (33-gal.) (optional)	125-litre (33-gal.) (optional)

CREW CAB, 6FT., 4IN. BOX – AIR SUSPENSION, 4x2 AND 4x4

TIRE SIZE: 275/55R20

Suspension Mode	Entry / Exit	Normal Ride Height	Off Road 1	Off Road 2
Wheelbase (nominal)	3,898 (153.5)	3,898 (153.5)	3,898 (153.5)	3,898 (153.5)
Track, Front	1,741 (68.5)	1,741 (68.5)	1,741 (68.5)	1,741 (68.5)
Track, Rear	1,729 (68.1)	1,729 (68.1)	1,729 (68.1)	1,729 (68.1)
Overall Length	6,142 (241.8)	6,142 (241.8)	6,142 (241.8)	6,142 (241.8)
Overall Width	2,084 (82.1)	2,084 (82.1)	2,084 (82.1)	2,084 (82.1)
Overall Height	1,922 (75.7)	1,968 (77.5)	1,993 (78.4)	2,019 (79.5)

CREW CAB, 6FT., 4IN. BOX – AIR SUSPENSION, 4x2 AND 4x4

TIRE SIZE: 275/55R20

Ground Clearance	Entry / Exit	Normal Ride Height	Off Road 1	Off Road 2
Front Axle	207 (8.1)	207 (8.1)	207 (8.1)	207 (8.1)
Rear Axle	220 (8.6)	220 (8.6)	220 (8.6)	220 (8.6)
Open Tailgate to Ground	832 (32.7)	871 (34.3)	889 (35.0)	922 (36.3)
Pickup Body Height	545 (21.4)	545 (21.4)	545 (21.4)	545 (21.4)
Approach Angle, degrees	14.5	18.9	21.5	23.1
Departure Angle, degrees	22.7	24.9	25.8	27.1

Ground Clearance	Entry / Exit	Normal Ride Height	Off Road 1	Off Road 2
Ramp Breakover Angle Without Skid Plate, degrees	15.5	18.7	20.6	22.1
Ramp Breakover Angle With Skid Plate, degrees	13.5	16.7	18.5	20.1
Ground Clearance Without Skid Plate	168 (6.6)	220 (8.6)	250 (9.8)	271 (10.7)
Ground Clearance With Skid Plate	155 (6.1)	207 (8.1)	237 (9.3)	259 (10.2)
Fuel Tank Capacity	87-litre (23-gal.) (standard) 98-litre (26-gal.) (standard) 125-litre (33-gal.) (optional)	87-litre (23-gal.) (standard) 98-litre (26-gal.) (standard) 125-litre (33-gal.) (optional)	87-litre (23-gal.) (standard) 98-litre (26-gal.) (standard) 125-litre (33-gal.) (optional)	87-litre (23-gal.) (standard) 98-litre (26-gal.) (standard) 125-litre (33-gal.) (optional)

INTERIOR DIMENSIONS

ACCOMMODATIONS

Model	Quad Cab	Crew Cab
Seating Capacity, F/R	3/3	3/3

FRONT

Front	Quad Cab	Crew Cab
Headroom	1,038 (40.9)	1,038 (40.9)
Legroom	1,040 (40.9)	1,040 (40.9)
Shoulder Room	1,676 (66.0)	1,676 (66.0)
Hip Room	1,610 (63.4)	1,610 (63.4)
Seat Travel	220 (8.7)	220 (8.7)
Recliner Range (degrees)	Total travel 71 degrees (from full forward) 18 degrees forward (from design) 53 degrees rearward (from design)	Total travel 71 degrees (from full forward) 18 degrees forward (from design) 53 degrees rearward (from design)

REAR

Rear	Quad Cab	Crew Cab
Headroom	995 (39.2)	1,011 (39.8)
Legroom	903 (35.6)	1,147 (45.2)
Shoulder Room	1,668 (65.7)	1,670 (65.7)
Hip Room	1,610 (63.4)	1,611 (63.4)

INTERIOR VOLUME

Interior Volume	Quad Cab	Crew Cab
Front – litres (cu. ft.)	1,809 (63.9)	1,809 (63.9)
Rear – litres (cu. ft.)	1,509 (53.3)	1,940 (68.5)

STEERING SPECIFICATIONS

QUAD CAB PICKUP

Measurement	2WD Short Bed	2WD Long Bed	4WD Short Bed	4WD Long Bed	4WD Rebel
Wheelbase (nominal; mm/in.)	3,569/140.5	3,569/140.5	3,569/140.5	3,569/140.5	3,569/140.5
Overall Ratio	16.3:1	16.3:1	16.3:1	16.3:1	17.8:1
Steering Wheel Turns (lock-to-lock)	3.1	3.1	3.1	3.1	3.4
18-in. Tire Turning Diameter (M / ft.)*	14.1 / 46.2	14.1 / 46.2	14.1 / 46.2	14.1 / 46.2	14.1 / 46.2
20-in. Tire Turning Diameter (M / ft.)*	13.74 / 45.1	13.74 / 45.1	13.74 / 45.1	13.74 / 45.1	NA

* = Curb-to-curb turning diameter is measured at the outside of the tires at curb height.
Turning diameters and steering wheel turns, lock-to-lock may differ with optional tires and wheels.

CREW CAB PICKUP

Measurement	2WD Short Bed	2WD Long Bed	4WD Short Bed	4WD Long Bed	4WD Rebel	TRX
Wheelbase (nominal)	144.6 / 3,672	153.5 / 3,898	144.6 / 3,572	153.5 / 3,898	144.6 / 3,572	145.1 / 3,685.5
Overall Ratio	16.3:1	15.5:1	16.3:1	15.5:1	17.8:1	16.3:1
Steering Wheel Turns (lock-to-lock)	3.1	2.9	3.1	2.9	3.4	3.1
18-in. Tire Turning Diameter (M / ft.)*	14.08 / 46.2	14.84 / 48.7	14.08 / 46.2	14.84 / 48.7	14.1 / 46.2	14.7 / 48.3

Measurement	2WD Short Bed	2WD Long Bed	4WD Short Bed	4WD Long Bed	4WD Rebel	TRX
20-in. Tire Turning Diameter (M / ft.)*	14.08 / 46.2	14.84 / 48.7	14.08 / 46.2	14.84 / 48.7	NA	NA

* = Curb-to-curb turning diameter is measured at the outside of the tires at curb height.
Turning diameters and steering wheel turns, lock-to-lock may differ with optional tires and wheels.

#