


LIGHTOLIER

Downlighting

Recessed & Surface

Product Selection Guide

Powerful portfolio of all-in-one selectable products to impress your toughest customer with CCT & lumen select on the fly.



Reference	
3	High applicability
2	Medium applicability
1	Low applicability
Blank	Non-applicable

	Budget-grade	Budget-grade	Budget-grade	Budget-grade	Budget-grade	Budget-grade	Value-grade															
	Good	Good	Good	Good	Good	Good	Good															
	Commercial Retrofit Downlight DualSelect	Retrofit Downlight	Flat Downlight Select	Mini Downlight	Mini Gimbal	Surface Mount	SlimSurface LED															
Applicability	Retail 3	Hospitality 1	Office 1	Education 1	Residential 3	Sizes 4", 6", 8", 10"	Shape Round	Color Temperature 3000K, 3500K, 4000K (CCT Field Selectable)	Lumen Range 500-3000lm (Lumen Field Selectable)	Efficacy up to 93lm/W	Reflector Option -	Trim Direct Cutoff -	Trim Reflected Cutoff -	Accent Adjustment -	CRI 90	SDCM 3	Emergency -	Life 50,000hrs	Tunable White -	Dimming 0-10V dim	Interact -	Link
Features / Performance	3	1	1	1	3	4", 5/6"	Round	Field Selectable 5CCT (2700K, 3000K, 3500K, 4000K, and 5000K)	700lm, 900lm	up to 78lm/W	-	-	-	-	90	3	-	50,000hrs	-	ELV/TRIAC	-	
Controls	3	1	1	1	3	3", 4", 5", 6", 8"	Round & Square	Field Selectable 5CCT (2700K, 3000K, 3500K, 4000K, and 5000K)	370-1300lm (Lumen Field Selectable)	up to 70lm/W	-	-	-	-	90	3	-	50,000hrs	-	ELV/Triac & 0-10V dim	-	
	2	3	3	3	3	3", 4", 6"	Round	Field Selectable 5CCT (2700K, 3000K, 3500K, 4000K, and 5000K)	(375-1185lm) (Lumen Field Selectable)	up to 70lm/W	-	-	-	-	90	3	-	50,000hrs	-	ELV/Triac & 0-10V dim	-	
	2	3	3	3	3	3", 4", 6"	Round	Field Selectable 5CCT (2700K, 3000K, 3500K, 4000K, and 5000K)	375-1185lm (Lumen Field Selectable)	up to 72lm/W	-	-	-	-	90	3	-	50,000hrs	-	ELV/Triac & 0-10V dim	-	
	1	1	1	1	3	5", 7", 9" 11", 14"	Round	Field Selectable 5CCT (2700K, 3000K, 3500K, 4000K, and 5000K)	700-2000lm (Lumen Field Selectable)	up to 74lm/W	-	-	-	-	90	3	-	50,000hrs	-	ELV/Triac & 0-10V dim	-	
	3	3	3	3	3	5", 7", 10" round 4", 6" square	Round, Square	2700K, 3000K, 3500K, 4000K	650lm, 1000lm, 2200lm	up to 95lm/W	-	-	-	-	80/90	3	-	50,000hrs	-	ELV/TRIAC/0-10V	remote via SBA	